Industrial Electrochemistry – Electrochemical Processes – Materials www.electrochem-technologies.com



ELECTROCHEM TECHNOLOGIES & MATERIAUX INC.

Électrochimie industrielle – Procédés électrochimiques – Matériaux www.electrochem-technologies.com

Safety Data Sheet

Vanadium electrolyte solution (Vanalyte™ and SuperVanalyte™)

1. Identification

Product identifier:	Vanadium electrolyte solution (Vanalyte™ and Supervanalyte™)
Product code:	
Recommended use:	Scientific research and development, electrolyte equimolar solution used for vanadium redox flow batteries (VRFB)
Restriction on use:	For scientific use
Supplier Name:	ELECTROCHEM TECHNOLOGIES & MATERIALS INC. 2037 avenue Aird, suite 201 Montréal, Québec Canada, H1V 2V9
Telephone:	514 251-9909
Emergency tel. number:	514 251-9909
Available hours:	9h00 - 17h00 Monday to Friday

2. Hazard identification

Signal word:	DANGER
Product classification:	
	Acute toxicity-inhalation - Category 3.
	Skin corrosion - Category 1A. Serious eye damage - Category 1. Health hazards not otherwise classified - Category 1 Corrosive. Corrosive to metals - Category 1.
	Reproductive toxicity - Category 2. Specific target organ toxicity – repeated exposure - Category 1.
	Acute toxicity-oral - Category 4.
Hazard statement(s):	H331 - Toxic if inhaled.
	H314 - Causes severe skin burns and eye damage.
	H374 - Causes serious injury to the respiratory tract.
	H290 - May be corrosive to metals.
	H361 - Suspected of damaging fertility or the unborn child.
	H372 - Causes damage to organs (lungs) through prolonged or repeated exposure.
	H302 - Harmful if swallowed.

Precautionary statement(s)

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep only in original packaging. Do not breathe mist, vapors and spray. Wash hands thoroughly after handling and any other part of the body that may have been exposed to the product. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves,

Industrial Electrochemistry – Electrochemical Processes – Materials www.electrochem-technologies.com



ELECTROCHEM TECHNOLOGIES & MATERIAUX INC. Électrochimie industrielle – Procédés électrochimiques – Matériaux

www.electrochem-technologies.com

Safety Data Sheet

Vanadium electrolyte solution (Vanalyte[™] and SuperVanalyte[™])

protective clothing, eye and face protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Immediately call a doctor. Wash contaminated clothing before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Immediately call a doctor. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or a doctor. IF exposed or concerned: Get medical advice. Absorb spillage to prevent material-damage.

Storage: Keep container tightly closed. Store in a well ventilated place. Store locked up. Store in a corrosive resistant container with a resistant inner liner.

Disposal: Dispose of contents/container in accordance with local, regional, national and/or international regulations in force.

Other hazards: Moderately toxic by intravenous, intraperitoneal route and subcutaneous routes.

See toxicological information, section 11

3. Composition/ Information on ingredients

No	CAS No :	Common name and synonyms	Concentration % (w/w)
1	7664-93-9	Sulfuric acid	14.00 - 22.00
2	13701-70-7	Divanadium(III) trisulfate	9.00 - 22.00
3	27774-13-6	Vanadium(IV) oxide sulfate. Oxovanadium(IV) sulfate. Vanadyl sulfate	9.00 - 20.00
4	7664-38-2	Phosphoric acid. Orthophosphoric acid. o-Phosphoric acid	0.10 - 1.00

4. First-aid measures

If swallowed, irritation, any type of overexposure or symptoms of overexposure occur during use of the product or persists after use, immediately contact a POISON CENTER, an EMERGENCY ROOM or a PHYSICIAN; ensure that the product safety data sheet is available.

Eye contact: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention as soon as possible.

Skin contact: Remove contaminated clothing immediately. Wash the skin with soap and water. Thoroughly wet contaminated clothing. If irritation persists, consult a doctor.

Inhalation: Move exposed person to fresh air. Keep this person warm and lying down. Loosen tight clothing such as a collar, tie, belt or waistband. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention immediately.

Ingestion: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting unless instructed by medical personnel.

Symptoms: This product is corrosive to skin, eyes, respiratory and digestive tracts. The severity of symptoms can vary depending on the exposure conditions (contact time, product concentration, etc.). Coughing, breathing pain. The main symptoms of intoxication include headache, nausea, vomiting, weakness, loss of appetite, fatigue, sweating, fever, tachycardia and dyspnea. In the most severe cases, convulsions, hyperthermic coma, liver damage are reported and sometimes death.

Effects (acute or delayed): If on skin, this product causes severe burns. Contact with eyes may cause redness, tearing, edema, pain, corneal opacity and even blindness. Inhalation of high concentrations vapors can cause severe burns to the mouth and airways leading to the lungs. May cause the inflammation of the airways. High concentration exposure can lead to severe lesions and ulcerations of the esophageal mucosa and gastrointestinal tract.



Industrial Electrochemistry – Electrochemical Processes – Materials www.electrochem-technologies.com



ELECTROCHEM TECHNOLOGIES & MATERIAUX INC.

Électrochimie industrielle – Procédés électrochimiques – Matériaux www.electrochem-technologies.com

Safety Data Sheet

Vanadium electrolyte solution (Vanalyte[™] and SuperVanalyte[™])

Immediate medical attention and special treatment: Probable mucosal damage may contraindicate the use of gastric lavage. Warning: risk of gastric perforation.

5. Fire-fighting measures

Suitable extinguishing media: Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media: Jets of water can facilitate the spread of fire.

Specific hazards arising from the hazardous product: May release dangerous fumes.

Hazardous combustion products: Sulfur oxides. Phosphine.

Special protective equipment and precautions for fire-fighters: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions: No action shall be taken involving any personal risk or if you do not have suitable training or protection. Evacuate surrounding areas. Do not touch or walk through spilled material. Shut off all heating and ignition sources. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Protective equipment and emergency procedures: Avoid dispersal of spilled material, runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution. Use inert absorbent or retention tubes in the event of a large spill.

Methods and materials for containment and cleaning up: Stop leak if without risk. Move containers from spill area. Contain leaks and pick up with non-combustible absorbent materials such as sand, earth or vermiculite. Then, place in an appropriate waste disposal container according to local regulations. Dispose of via a licensed waste disposal contractor.

7. Handling and storage

Precautions for safe handling: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure - obtain special instructions before use. Avoid contact with eyes, skin and clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

The handling of this product must comply with local regulations. Store in an airtight container located in a dry, well ventilated and soil corrosion resistant cemented. Refer to the storage of the ROHS standards and NFC. Keep away from combustible materials and bases. If the product is stored with other dangerous substances, refer to the NFC segregation table. Containers for corrosive substances shall be kept closed, carry clear identification of their contents and be handled with care. Note: this product attacks certain types of plastic, rubber or coating.

Conditions for safe storage: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Incompatibility: Bases. Reductive agents. Halogenated products. Carbides. Finely divided metals (Ba, Be, Na, K, P, Al, Mg etc). Peroxides. Alcohols and amines.



Industrial Electrochemistry – Electrochemical Processes – Materials www.electrochem-technologies.com



ELECTROCHEM TECHNOLOGIES & MATERIAUX INC. Électrochimie industrielle – Procédés électrochimiques – Matériaux

Istrielle – Procedes electrochimiques – Materiaux www.electrochem-technologies.com

Safety Data Sheet

Vanadium electrolyte solution (Vanalyte[™] and SuperVanalyte[™])

8. Exposure Controls/ Personal protection

Alberta

No	CAS No :	Common name and synonyms	8-hour occupational exposure limit (TWA)					Ceiling ccupational exposure limit	
			ppm	mg/m³	ppm	mg/m³	ppm	mg/m³	
1	7664-93-9	Sulfuric acid	Not listed	1	Not listed	3	Not listed	Not listed	
2	13701-70-7	Divanadium(III) trisulfate	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed	
3	27774-13-6	Vanadium(IV) oxide sulfate. Oxovanadium(IV) sulfate. Vanadyl sulfate	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed	
4	7664-38-2	Phosphoric acid. Orthophosphoric acid. o- Phosphoric acid	Not listed	1	Not listed	3	Not listed	Not listed	

British-Columbia

No	CAS No :	Common name and synonyms	8-hour occupational exposure limit (TWA)				Ceiling ccupational exposure limit	
			ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m³
1	7664-93-9	Sulfuric acid	Not listed	0.2	Not listed	Not listed	Not listed	Not listed
2	13701-70-7	Divanadium(III) trisulfate	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
3	27774-13-6	Vanadium(IV) oxide sulfate. Oxovanadium(IV) sulfate. Vanadyl sulfate	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
4	7664-38-2	Phosphoric acid. Orthophosphoric acid. o- Phosphoric acid	Not listed	1	Not listed	3	Not listed	Not listed

Ontario

No	CAS No :	Common name and synonyms	8-hour occupational exposure limit (TWA)				Ceiling ccupational exposure limit	
			ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
1	7664-93-9	Sulfuric acid	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
2	13701-70-7	Divanadium(III) trisulfate	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
3	27774-13-6	Vanadium(IV) oxide sulfate. Oxovanadium(IV) sulfate. Vanadyl sulfate	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
4	7664-38-2	Phosphoric acid. Orthophosphoric acid. o- Phosphoric acid	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed

Industrial Electrochemistry – Electrochemical Processes – Materials

www.electrochem-technologies.com



ELECTROCHEM TECHNOLOGIES & MATERIAUX INC. Électrochimie industrielle – Procédés électrochimiques – Matériaux

www.electrochem-technologies.com

Safety Data Sheet

Vanadium electrolyte solution (Vanalyte[™] and SuperVanalyte[™])

Quebec

No	CAS No :	Common name and synonyms	8-hour occupational exposure limit (TWA)		•			Ceiling ccupational exposure limit	
			ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³	
1	7664-93-9	Sulfuric acid	Not listed	0.2	Not listed	3	Not listed	Not listed	
2	13701-70-7	Divanadium(III) trisulfate	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed	
3	27774-13-6	Vanadium(IV) oxide sulfate. Oxovanadium(IV) sulfate. Vanadyl sulfate	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed	
4	7664-38-2	Phosphoric acid. Orthophosphoric acid. o- Phosphoric acid	Not listed	1	Not listed	3	Not listed	Not listed	

Saskatchewan

No	CAS No :	Common name and synonyms	8-hour occupational exposure limit (TWA)					Ceiling ccupational exposure limit	
			ppm	mg/m ³	ppm	mg/m³	ppm	mg/m ³	
1	7664-93-9	Sulfuric acid	Not listed	0.2	Not listed	0.6	Not listed	Not listed	
2	13701-70-7	Divanadium(III) trisulfate	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed	
3	27774-13-6	Vanadium(IV) oxide sulfate. Oxovanadium(IV) sulfate. Vanadyl sulfate	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed	
4	7664-38-2	Phosphoric acid. Orthophosphoric acid. o- Phosphoric acid	Not listed	1	Not listed	3	Not listed	Not listed	

United States

No	CAS No :	Common name and synonyms	IDLH	R	egulatory	Limits	Recommer	nded Limits
			NIOSH	OSHA	A PEL	California / OSHA PEL	NIOSH REL	ACGIH ® 2019 TLV ®
				ppm	mg/m ³	8-hour TWA (ST) STEL (C) Ceiling	Up to 10-hour TWA (ST) STEL (C) Ceiling	8-hour TWA (ST) STEL (C) Ceiling
1	7664-93-9	Sulfuric acid	15	Not listed	1	0.1 mg/m3 (ST) 3 mg/m3	1 mg/m3	0.2 mg/m3 (Thor.)
2	13701-70-7	Divanadium(III) trisulfate	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
3	27774-13-6	Vanadium(IV) oxide sulfate. Oxovanadium(IV) sulfate. Vanadyl sulfate	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
4	7664-38-2	Phosphoric acid. Orthophosphoric acid. o- Phosphoric acid	4008	Not listed	1	1 mg/m3 (ST) 3 mg/m3	1 mg/m3 (ST) 3 mg/m3	1 mg/m3 (ST) 3 mg/m3

IDLH: Immediately Dangerous to Life or Health Concentrations NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration PEL: Permissible Exposure Limits



K

Industrial Electrochemistry – Electrochemical Processes – Materials www.electrochem-technologies.com



ELECTROCHEM TECHNOLOGIES & MATERIAUX INC.

Électrochimie industrielle – Procédés électrochimiques – Matériaux www.electrochem-technologies.com

Safety Data Sheet

Vanadium electrolyte solution (Vanalyte[™] and SuperVanalyte[™])

California / OSHA: California Division of Occupational Safety and Health

REL: Recommended Exposure Limits ACGIH ®: American Conference of Governmental Industrial Hygienists TLV ®: Threshold Limit Values

Appropriate engineering controls: When a worker is exposed to a substance identified as having a demonstrated or suspected carcinogenic, mutagenic and/or reprotoxic effect on humans, exposure must be kept to a minimum, even when it remains within the expected standards regardless of the duration of exposure. Recirculation must be prohibited. Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eyes: DO NOT WEAR CONTACT LENSES. Wear anti-splash safety goggles.

Hands: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties.

Respiratory: If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Others: Wear protective clothing with long sleeves and appropriate safety shoes at all times.

9. Physical and chemical properties

Physical state: Liquid Colour: Dark blue to bluish green Odour: Faint metallic odor Melting/Freezing point: -10 °C (14 °F) Initial boiling point/boiling range: 105 - 110 °C (221 - 230 °F) Flammability: Not applicable Lower flammable/explosive limit: Not applicable Upper flammable/explosive limit: Not applicable Flash point: Not applicable Auto-ignition temperature: Not applicable Decomposition temperature: > 265 °C (509 °F) **pH:** < 1 Kinematic viscosity: 1.10 - 1.75 mm²/s (at 40 °C) Solubility: Miscible Partition coefficient - n-octanol/water (Log Kow): Not applicable Vapour pressure: 17.3 mm Hg at 20 °C Density and relative density: 1,250 - 1,610 kg/L at 20 °C (water = 1) Relative vapour density: > 1 (air = 1) Particle characteristics: Not applicable



Industrial Electrochemistry – Electrochemical Processes – Materials www.electrochem-technologies.com



ELECTROCHEM TECHNOLOGIES & MATERIAUX INC.

Électrochimie industrielle – Procédés électrochimiques – Matériaux www.electrochem-technologies.com

Safety Data Sheet

Vanadium electrolyte solution (Vanalyte[™] and SuperVanalyte[™])

10. Stability and reactivity

Reactivity: Stable under recommended conditions of storage and handling.

Chemical stability: The product is chemically stable under normal conditions of use. This product is unstable under the following conditions: The product decomposes when exposed to heat.

Possibility of hazardous reactions: No dangerous or polymerization reactions will not occur under normal conditions of use. May react violently or explode upon contact many organic and inorganic compounds. Emits toxic fumes when heated.

Conditions to avoid: Keep away from incompatible products (see section 7).

Incompatible materials: This product attacks metals.

Hazardous decomposition products: Sulfur oxides. Phosphorus oxide.

11. Toxicological information

	Oral	Dermal	Inhalation gases	Inhalation vapours	Inhalation dusts/mists
ATE _{product}	1249.84 mg/kg	20578.9 mg/kg	N/A	2.27 mg/l	1.18 mg/l

No	CAS No :	Common name and synonyms	LD₅₀ oral mg/kg	LD₅₀ skin mg/kg	LC ₅₀ inhalation ppmV 4h - gases	LC ₅₀ inhalation mg/l 4h - vapours	LC ₅₀ inhalation mg/l 4h - dusts-mist
1	13701-70-7	Divanadium(III) trisulfate	> 5000	> 5000	N/A	N/A	> 5.00
2	7664-93-9	Sulfuric acid	2140	> 5000	N/A	0.5	0.26
3	27774-13-6	Vanadium(IV) oxide sulfate. Oxovanadium(IV) sulfate. Vanadyl sulfate	288	4450	N/A	N/A	> 5.00
4	7664-38-2	Phosphoric acid. Orthophosphoric acid. o-Phosphoric acid	3500	2740	N/A	N/A	> 5.00

Routes of exposure: This product is absorbed through the respiratory tract and by the digestive tract. However, it is unlikely that the product will be absorbed into the body to any significant extent since it exerts a local action which destroys the tissues.

Symptoms: This product is corrosive to skin, eyes, respiratory and digestive tracts. The severity of symptoms can vary depending on the exposure conditions (contact time, product concentration, etc.). Coughing, breathing pain. The main symptoms of intoxication include headache, nausea, vomiting, weakness, loss of appetite, fatigue, sweating, fever, tachycardia and dyspnea. In the most severe cases, convulsions, hyperthermic coma, liver damage are reported and sometimes death.

Delayed and immediate effects: If on skin, this product causes severe burns. Contact with eyes may cause redness, tearing, edema, pain, corneal opacity and even blindness. Inhalation of high concentrations vapors can cause severe burns to the mouth and airways leading to the lungs. May cause the inflammation of the airways. High concentration exposure can lead to severe lesions and ulcerations of the esophageal mucosa and gastrointestinal tract.



Industrial Electrochemistry – Electrochemical Processes – Materials

www.electrochem-technologies.com



ELECTROCHEM TECHNOLOGIES & MATERIAUX INC. Électrochimie industrielle – Procédés électrochimiques – Matériaux

www.electrochem-technologies.com

Safety Data Sheet

Vanadium electrolyte solution (Vanalyte™ and SuperVanalyte™)

Aspiration hazard	N/A
Skin corrosion - Skin irritation	Yes
Serious eye damage - Serious eye irritation - Eye irritation	Yes
Skin sensitization	N/A
Respiratory sensitization	N/A
Specific target organ toxicity – single exposure	N/A
Specific target organ toxicity – single exposure Category 3 Narcotic effects	N/A
Specific target organ toxicity – single exposure Category 3 Respiratory tract irritation	N/A
Specific target organ toxicity – repeated exposure	Yes

No	CAS No :	Common name and synonyms	IARC	ACGIH	Mutagenicity	Effect on reproduction	
1	13701-70-7	Divanadium(III) trisulfate	Not listed	Not listed	No effects shown.	Possible risk of impaired fertility.	
2	7664-93-9	Sulfuric acid	Not listed	Not listed	No effects shown.	No effects shown.	
3	27774-13-6	Vanadium(IV) oxide sulfate. Oxovanadium(IV) sulfate. Vanadyl sulfate	Not listed	Not listed	No effects shown.	Possible risk of impaired fertility.	
4	7664-38-2	Phosphoric acid. Orthophosphoric acid. o-Phosphoric acid	Not listed	Not listed	No effects shown.	No effects shown.	

Cancer classification under IARC (International Agency for Research on Cancer)

Group 1: carcinogenic to humans.

Group 2A: probably carcinogenic to humans.

Group 2B: possibly carcinogenic to humans.

Group 3: not classifiable as to its carcinogenicity to humans.

Group 4: probably not carcinogenic to humans.

Cancer classification under ACGIH (American Conference of Governmental Industrial Hygienists)

Group A1: confirmed human carcinogen.

Group A2: suspected human carcinogen.

Group A3: confirmed animal carcinogen with unknown relevance to humans.

Group A4: not classifiable as a human carcinogen.

Group A5: not suspected as a human carcinogen.



Industrial Electrochemistry – Electrochemical Processes – Materials www.electrochem-technologies.com



ELECTROCHEM TECHNOLOGIES & MATERIAUX INC.

Électrochimie industrielle – Procédés électrochimiques – Matériaux www.electrochem-technologies.com

Safety Data Sheet

Vanadium electrolyte solution (Vanalyte[™] and SuperVanalyte[™])

12. Ecological information

Ecotoxicity

No	CAS No :	Common name and synonyms	%	Aquatic Ecotoxicity short term	Aquatic Ecotoxicity long term	Terrestrial Ecotoxicity
1	13701-70-7	Divanadium(III) trisulfate	9.00 - 22.00	Not available.	Toxic to aquatic life with long lasting effects.	No known adverse effect to the environment.
2	7664-93-9	Sulfuric acid	14.00 - 22.00	No known adverse effect to aquatic life.	No known adverse effect to aquatic life.	No known adverse effect to the environment.
3	27774-13-6	Vanadium(IV) oxide sulfate. Oxovanadium(IV) sulfate. Vanadyl sulfate	9.00 - 20.00	Not available.	Toxic to aquatic life with long lasting effects.	No known adverse effect to the environment.
4	7664-38-2	Phosphoric acid. Orthophosphoric acid. o-Phosphoric acid	0.10 - 1.00	No known adverse effect to aquatic life.	No known adverse effect to aquatic life.	No known adverse effect to the environment.

Persistence and degradability. Bioaccumulative potential. Other adverse effects

No	CAS No :	Common name and synonyms	%	Persistent	Bio- accumulation	Aquatic ecotoxicity
1	13701-70-7	Divanadium(III) trisulfate	9.00 - 22.00	N/A	N/A	N/A
2	7664-93-9	Sulfuric acid	14.00 - 22.00	Yes	No	No
3	27774-13-6	Vanadium(IV) oxide sulfate. Oxovanadium(IV) sulfate. Vanadyl sulfate	9.00 - 20.00	Yes	No	Yes
4	7664-38-2	Phosphoric acid. Orthophosphoric acid. o-Phosphoric acid	0.10 - 1.00	Yes	No	No

Degradability: N/A

Mobility in soil: N/A

13. Disposal considerations

Methods of disposal: The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.





Industrial Electrochemistry – Electrochemical Processes – Materials www.electrochem-technologies.com *

ELECTROCHEM TECHNOLOGIES & MATERIAUX INC. Électrochimie industrielle – Procédés électrochimiques – Matériaux www.electrochem-technologies.com

Safety Data Sheet

Vanadium electrolyte solution (Vanalyte™ and SuperVanalyte™)

14. Transport information

	TDG	DOT	IMDG	ΙΑΤΑ
UN Number	3264	3264	3264 3264	
Proper shipping name	CORROSIVE LIQUID,	CORROSIVE LIQUID,	CORROSIVE LIQUID,	CORROSIVE LIQUID,
	ACIDIC, INORGANIC,	ACIDIC, INORGANIC,	NIC, ACIDIC, INORGANIC, ACIDIC, INORGAN	
	N.O.S. (Sulfuric acid)	N.O.S. (Sulfuric acid)	N.O.S. (Sulfuric acid)	N.O.S. (Sulfuric acid)
Transport hazard class(es)	8	8	8	8
Packing group	II	II	II	II

Canada - ERAP

Not applicable

United States - Reportable Quantities (RQ)

No	CAS No :	Common name and synonyms	RQ lbs (kg)
1	7664-93-9	Sulfuric acid	1000 (454)
2	7664-38-2	Phosphoric acid. Orthophosphoric acid. o-Phosphoric acid	5000 (2270)

Transport in bulk (according to Annex II of the International Convention for the Prevention of Pollution From Ships, 1973, as modified by the Protocol of 1978 (MARPOL 73/78), and the International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk (IBC Code)): N/A

Marine pollutant: No

Exemption for limited quantity: 1 L

In accordance with the Canadian Transport of Dangerous Goods regulations by Road, we use the 1.17 exemption when applicable. In accordance with 49 CFR article 172.315 for transportation by a mode other than air, we use the Limited quantities exemption when applicable.

Other exemptions: No other exemption.

Special precautions: Not applicable

15. Regulatory information



Industrial Electrochemistry – Electrochemical Processes – Materials

www.electrochem-technologies.com



ELECTROCHEM TECHNOLOGIES & MATERIAUX INC. Électrochimie industrielle – Procédés électrochimiques – Matériaux

www.electrochem-technologies.com

Safety Data Sheet

Vanadium electrolyte solution (Vanalyte[™] and SuperVanalyte[™])

Canada

No	CAS No :	Common name and synonyms	%	DSL	NDSL	NPRI
1	13701-70-7	Divanadium(III) trisulfate	9.00 - 22.00		Х	
2	7664-93-9	Sulfuric acid	14.00 - 22.00	Х		Х
3	27774-13-6	Vanadium(IV) oxide sulfate. Oxovanadium(IV) sulfate. Vanadyl sulfate	9.00 - 20.00	Х		
4	7664-38-2	Phosphoric acid. Orthophosphoric acid. o-Phosphoric acid	0.10 - 1.00	Х		

United States

No	CAS No :	Common name and synonyms	%	TSCA	PROP-65	RTK
1	13701-70-7	Divanadium(III) trisulfate	9.00 - 22.00	Х		
2	7664-93-9	Sulfuric acid	14.00 - 22.00	Х		Х
3	27774-13-6	Vanadium(IV) oxide sulfate. Oxovanadium(IV) sulfate. Vanadyl sulfate	9.00 - 20.00	Х		Х
4	7664-38-2	Phosphoric acid. Orthophosphoric acid. o-Phosphoric acid	0.10 - 1.00	Х		Х

The customer is responsible for determining the PPE (personal protection equipment) code for this material.

The classification of the product and the SDS were developped in accordance with HPR and HazCom 2012.

16. Other information

Date: 2023-08-09

Version: 1

Notice to reader: The manufacturer hereby declares that the information disclosed herein have been based on governmental sites and/or raw material supplier's. The manufacturer has no control over the nature and content of such information. The manufacturer fully reproduces all the information it holds on the constituent of the product, at the time it is manufactured. The manufacturer does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. By this data sheet, the manufacturer hereby discloses all the potential dangers it has knowledge of and which might be related to the using or manipulation of the product in order to allow the proper care to be brought and use with regard to the product. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist and notification is hereby given to the user. Notice is hereby given that injury can derive therefrom if the foregoing is not respected. The manufacturer assumes no responsibility for personal and/or material damage, lost or injury of whichever nature caused or which may occur following the wrongful, inappropriate, negligent or abusive use or handling of the product or from not having read the herein contained information.